

TS Series



300 Series Stainless Steel, Half-Door Refrigerators

Model	Swing Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H*
SOLID HALF DOORS									
TS-23-2	2 s/s	23	3	1/3	7.5	300	27	29 1/2	78 1/4
TS-49-4	4 s/s	49	6	1/2	9.5	470	54	29 1/2	78 1/4
TS-72-6	6 s/s	72	9	1/2	11.8	621	78	29 1/2	79 1/4
GLASS HALF DOORS									
TS-23G-2	2 gls	23	3	1/3	7.9	296	27	29 1/2	78 1/4
TS-49G-4	4 gls	49	6	1/2	10.0	515	54	29 1/2	78 1/4
TS-72G-6	6 gls	72	9	1/2	12.9	745	78	29 1/2	79 1/4
COMBINATION HALF DOORS									
TS-23-1-G-1	1 gls - 1 s/s	23	3	1/3	8.0	290	27	29 1/2	78 1/4
TS-49-2-G-2	2 gls - 2 s/s	49	6	1/2	10.0	500	54	29 1/2	78 1/4
TS-72-3-G-3	3 gls - 3 s/s	72	9	1/2	12.9	648	78	29 1/2	79 1/4

All dimensions rounded up to the nearest 1/8".

* Height does not include 5" for castor height or 6" for optional legs.
 † Depth does not include 1 3/8" for door handle (glass door models only).



TS-23-2



TS-49-2-G-2

True's
300 Series
Stainless Steel
Reach-In's



TS-72-6

FEATURES/BENEFITS

- **Oversized and balanced, environmentally friendly (134A), refrigeration system**, factory sealed and pre-lubricated for long life - holds **33°F to 38°F**.
- True's "TS" series is the choice for the exclusive 300 series stainless steel commercial application. Designed with enduring quality that protects your long-term investment, and oversized refrigeration that guarantees superior food preservation.
- **300 series stainless steel interior and exterior** front & sides, with matching aluminum back.
- **Energy efficient, "Low-E", thermal glass on glass door models.**
- **Solar, digital thermometer** standard for easy visibility.
- Incandescent interior lighting on solid door models.
- Fluorescent interior lighting; **integrated door light (IDL)** standard on glass & combination door models.
- **Bottom mount compressor.**
- Adjustable, **heavy duty, PVC coated wire shelves.**
- Positive seal self-closing doors with factory tested (over 1,000,000 times) **lifetime guaranteed door hinges and torsion type closure system.**
- **Lifetime guaranteed recessed door handles** on solid doors.
- Extruded, aluminum door frames on glass doors.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Door locks standard.
- **4" diameter swivel castors** standard equipment. 6" legs available.
- Self-contained system.
- Alternative hinge orientations available (contact factory).

Remote cabinets available 14% off list (condensing units supplied by others). Consult factory technical service dept. for BTU information.